

Thermo Scientific launches Rheometer series for quality control labs

10 June 2019 | News

Thermo Scientific HAAKE MARS iQ Rheometer series provides more analytical capabilities for QC and reliable, user-independent results



The Thermo Scientific HAAKE MARS iQ Rheometer was specifically designed to meet the needs of QC labs with built-in features that assist users to deliver more reliable results. Key features such as touchscreen control that allows users to quickly execute standard operating procedures (SOPs) and intuitive "Connect Assist" functionalities mean QC lab technicians can deliver more consistent and reliable results, even in busy labs with multiple operators running tests.

"The capabilities of the new HAAKE MARS iQ Rheometer series were expanded to equip customers with an extremely capable and reliable QC instrument that can be customized for a lab's needs today and in the future," said Hanna Granö-Fabritius, senior business director of material characterization at Thermo Fisher Scientific.

Those capabilities include:

- **An intuitive, multilingual 7-inch touchscreen** which allows users to run SOPs directly from the instrument with step-by-step guidance. The unique touchscreen on the instrument also shows instructions with images from the customer's own lab to clearly illustrate how to do the analysis correctly, step-by-step, for each user that is specific to that lab's process.
- **"Assist" functionalities** that provide lab technicians comprehensive guidance to reduce user errors. For example, the Connect Assist for temperature modules and measuring geometries allows technicians to quickly change accessories with quick coupling, automatic recognition and accurate alignment.
- **Advanced testing methods** and normal force capabilities measure axial forces in two directions. This supports texture analysis for sample bending, breaking and squeezing tests or tribology measurements for testing friction, lubrication and wear.
- **A newly designed frame and lift mechanism** provide high vibrational damping, minimal temperature expansion and higher chemical resistance to help ensure consistent results.